


NOTES

1. THIS INSTALLATION SHALL BE ACCESSIBLE FOR MAINTENANCE AND INSPECTION AT ALL TIMES.
2. WHERE SUBJECT TO VEHICLE LOADING, DESIGN ADEQUACY SHALL BE VERIFIED.
3. THE PERIMETER SHALL SLOPE AWAY FROM THE INTERCEPTOR. FLOW SHALL NOT INCLUDE SANITARY SEWAGE OR SURFACE DRAINAGE.
4. EACH INSTALLATION SHALL BE SIZED ACCORDING TO APPENDIX H OF THE UNIFORM PLUMBING CODE AND SHALL BE SUBJECT TO REVIEW BY THE CITY FOR ADEQUATE CAPACITY PRIOR TO CONSTRUCTION. MINIMUM CAPACITY SHALL BE 750 GALLONS.
5. A SAMPLING BOX IS REQUIRED IN ADDITION TO INTERCEPTOR.
6. A TWO COMPARTMENT INTERCEPTOR IS THE MINIMUM STANDARD.
7. EACH COMPARTMENT SHALL HAVE A SEPARATE RING AND COVER.

	CITY of CHINO	
	GREASE INTERCEPTOR	
(909) 334-3251	13220 Central Avenue, Chino, CA 91710	
Fax (909) 334-3729	7/01/2025	1 of 1